







ISO 4184 – DIN 7753 – BS 3790 – RMA IP22

In addition to their precision-built qualities, Fenner Power Plus **PB** Wedge Belts have superior anti-static and oil-resistant properties. All Fenner Power Plus, CRE Plus & Quattro Plus wedge belts are static conductive to **ISO 1813**, will not self-ignite under severe slip/stall conditions, and conform to American Petroleum Institute specifications. 

								
SPZ		SPA		SPB		SPC		
Belt Designation		Belt Designation		Belt Designation	Belt Designation	Belt Designation		Belt Designation
Metric	Imperial 3V	Metric	Imperial 3V			Metric	Imperial 5V	
487	-	1400	-	732	1750	1250	-	2000
512	-	1412	-	757	1757	1260	5V500	2120
562	-	1420	560	782	1782	1320	-	2240
587	-	1437	-	800	1800	1340	530	2360
612	-	1462	-	807	1807	1400	-	2500
630	3V250	1470	580	825	1832	1410	560	2650
637	-	1487	-	832	1850	1500	-	2800
662	-	1500	-	850	1857	1550	-	3000
670	-	1512	-	857	1882	1600	630	3150
687	-	1520	600	875	1900	1670	-	3350
710	280	1537	-	882	1907	1700	-	3550
722	-	1560	617	900	1932	1750	-	3750
737	-	1587	-	907	1950	1800	710	4000
750	-	1600	630	925	1957	1850	-	4250
760	300	1612	-	932	1982	1900	-	4500
772	-	1637	-	950	2000	1950	-	4750
787	-	1650	650	957	2032	2000	-	5000
800	315	1662	-	975	2057	2020	800	5300
812	-	1687	-	982	2060	2060	-	5600
825	-	1700	670	1000	2082	2120	-	6000
837	-	1737	-	1007	2120	2150	850	6300
850	-	1762	-	1030	2132	2240	-	6700
862	-	1787	-	1060	2180	2280	900	7100
875	-	1800	710	1082	2207	2360	-	7500
887	-	1812	-	1082	2207	2360	-	8000
900	355	1837	-	1090	2232	2410	950	8500
912	-	1850	730	1107	2240	2450	-	9000
925	-	1862	-	1120	2282	2500	-	9500
940	370	1887	-	1132	2300	2530	1000	10000
950	-	1900	750	1150	2307	2580	-	10600
962	-	1937	-	1157	2332	2650	-	11200
987	-	1987	800	1180	2360	2680	1060	11800
1000	-	2000	-	1207	2382	2720	-	12500
1010	400	2030	-	1220	2430	2840	1120	
1024	-	2037	-	1232	2482	2900	-	
1037	-	2120	-	1257	2532	3000	1180	
1047	-	2137	-	1272	2580	3150	-	
1060	-	2160	850	1272	2580	3170	1250	
1080	425	2187	-	1280	2607	3250	1320	
1087	-	2240	-	1307	2632	3350	-	
1112	-	2262	-	1320	2650	3450	1400	
1120	-	2280	900	1332	2682	3550	-	
1140	450	2287	-	1357	2720	3750	1500	
1162	-	2360	-	1360	2732	3800	-	
1180	-	2410	950	1382	2782	3870	-	
1187	-	2500	-	1407	2832	4000	-	
1200	475	2540	1000	1432	2847	4060	1600	
1212	-	2650	-	1450	2882	4250	-	
1237	-	2690	1060	1457	2900	4310	1700	
1250	-	2800	-	1482	2932	4500	-	
1262	-	2840	1120	1500	2982	4560	1800	
1270	500	3000	1180	1507	3000	4750	-	
1287	-	3150	-	1532	3032	4820	1900	
1312	-	3170	1250	1550	3082	5000	-	
1320	-	3350	-	1557	3150	5070	2000	
1340	530	3550	1400	1582	3182	5300	-	
1347	-	-	-	1607	3282	5380	2120	
1362	-	-	-	1632	3350	5680	-	
1387	-	-	-	1650	3382	5800	2240	
				1657	3750	6000	2360	
				1682	4000	6340	2500	
				1700	4250	6700	-	
				1707	4500	7500	2800	
				1732	-	8000	-	

	
8V/Delta	
Belt Designation	
Metric	Imperial 8V
2540	1000
2840	1120
3180	1250
3550	1400
3810	1500
4060	1600
4570	1800
5080	2000
5690	2240
6350	2500
7100	2800
8000	3150
9000	3550
10160	4000
11430	4500

Section dimensions in millimetres.

Metric designations show pitch length in mm. Imperial designations show 'effective' length in 1/10 inches

Note: The ISO 4184 standard now refers to 'datum' lengths, which are essentially the same as 'pitch' lengths